

Micrometer 40 AG

DIN
863-1



Features

- Lacquered steel frame
- Spindle and anvil made of hardened steel, carbide tipped
- Scales with satin-chrome finish
- Heat insulators
- Ratchet is integrated in the thimble
- Locking device
- Supplied with:
Case, setting standard

Note:

All Micrometers with measuring ranges between 400 mm to 500 mm, the frame is made from a steel tube

Technical Data

Measuring range mm	Readings mm	Error limit G μm	Spindle thread pitch mm	Order no.
200 - 225	0.01	8	0.5	4134500
225 - 250	0.01	8	0.5	4134501
250 - 275	0.01	9	0.5	4134502
275 - 300	0.01	9	0.5	4134503
300 - 325	0.01	10	0.5	4134504
325 - 350	0.01	10	0.5	4134505
350 - 375	0.01	11	0.5	4134506
375 - 400	0.01	11	0.5	4134507
400 - 425	0.01	12	0.5	4134508
425 - 450	0.01	12	0.5	4134509
450 - 475	0.01	13	0.5	4134510
475 - 500	0.01	13	0.5	4134511

Dimensions

Dimensions in mm	a	b	c	d	e
200 - 225	242.5	121.5	25	5	12
225 - 250	267.5	134	25	5	12
250 - 275	317.5	159	25	5	25
275 - 300	317.5	159	25	5	12
300 - 325	342.5	171.5	25	5	12
325 - 350	367.5	184	25	5	12
350 - 375	392.5	196.5	25	5	12
375 - 400	417.5	209	25	5	12
400 - 425	442	223	25	5	12
425 - 450	467	236	25	5	12
450 - 475	492	248	25	5	12
475 - 500	517	259	25	5	12

